

No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Plastic-Metal F Hardener (GB)

Code-Nr. 101502

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

info@weicon.de

1.4. Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38 R43 **R-phrases** 

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

#### 2.2. Label elements

# Labelling according to 1999/45/EC

# Remarks for labelling

The product is classified and labelled in accordance with EC directives.

Xi Irritant

R-phrases

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

S-phrases

Avoid contact with skin.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37/39 Wear suitable gloves and eye/face protection.

46 If swallowed, seek medical advice immediately and show this container or label.

# Hazardous ingredients for labeling

3,6-diazaoctanethylenediamin



No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

#### 2.3. Other hazards

#### Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

# 3.2. Mixtures

# **Description**

Modified polyamine

## Hazardous ingredients

| CAS No     | EC No     | Name                                  | [%<br>weight] | Classification according to 67/548/EEC                                                  |
|------------|-----------|---------------------------------------|---------------|-----------------------------------------------------------------------------------------|
| 90-72-2    | 202-013-9 | 2,4,6-tris(dimethylaminomethyl)phenol | 1 - 5         | Xn R22; Xi R36/38                                                                       |
| 112-24-3   | 203-950-6 | 3,6-diazaoctanethylenediamin          | 5 - 15        | Xn R21; C R34; R43; R52-53                                                              |
| 14807-96-6 | 238-877-9 | talcum (Mg3H2(SiO3)4)                 | 40 - 60       | -                                                                                       |
| CAS No     | EC No     | Name                                  | [%<br>weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]                      |
| 90-72-2    | 202-013-9 | 2,4,6-tris(dimethylaminomethyl)phenol | 1 - 5         | Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315                           |
| 112-24-3   | 203-950-6 | 3,6-diazaoctanethylenediamin          | 5 - 15        | Acute Tox. 4, H312 / Skin Corr. 1B, H314 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412 |
| 14807-96-6 | 238-877-9 | talcum (Mg3H2(SiO3)4)                 | 40 - 60       | -                                                                                       |

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

# In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

# In case of ingestion

Give activated charcoal.

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

# 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# 4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Use breathing apparatus with independent air supply (isolated).

#### **Additional information**

Collect contaminated firefighting water separately, must not be discharged into the drains.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

# 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

# 6.4. Reference to other sections

No information available.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

# Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

# General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Do not inhale dust.

## **Hygiene measures**

At work do not eat, drink and smoke.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

Pay attention to general rules of internal fire prevention.



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

# 7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

#### Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

### Further information on storage conditions

Keep container tightly closed.

Storage temperature between 2°C to 40°C

#### 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

| CAS No     | Name                 | Code    | [mg/m3] | [ppm] | Remark    |
|------------|----------------------|---------|---------|-------|-----------|
| 14807-96-6 | Talc respirable dust | 8 hours | 1       | •     | EH40/2005 |

#### 8.2. Exposure controls

## Respiratory protection

If ventilation insufficient, wear respiratory protection.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

# Eye protection

tightly fitting goggles protective shield

## Skin protection

Light protective clothing.

Safety shoes.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Form Colour Odour
pasty green hardly noticeable

# Important health, safety and environmental information

|                            | Value    | Temperature | at | Method    | Remark       |
|----------------------------|----------|-------------|----|-----------|--------------|
| pH value in delivery state | 11 - 12  | 20 °C       |    |           | 1:1 in water |
| decomposition point        | > 200 °C |             |    |           |              |
| Flash point                | > 100 °C |             |    | DIN 51758 |              |
| Solubility in water        |          | 20 °C       |    |           | miscible     |

#### 9.2. Other information

No information available.



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

# 10.3. Possibility of hazardous reactions

No information available.

#### 10.4. Conditions to avoid

No information available.

#### 10.5. Incompatible materials

#### Materials to avoid

Reactions with strong acids and alkalies. Reactions with strong oxidising agents.

### 10.6. Hazardous decomposition products

Smoke.

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

# Thermal decomposition

Remark No decomposition below 200°C.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

### Acute toxicity/Irritability/Sensitization

|                    | Value/Validation | Species    | Method | Remark |
|--------------------|------------------|------------|--------|--------|
| LD50 acute oral    | > 5000 mg/kg     | rat        |        |        |
| Irritability skin  | irritant         | rabbit     |        |        |
| Irritability eye   | irritant         | rabbit eye |        |        |
| Skin sensitization | sensitizing      | Guinea pig |        |        |

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

No information available.

### 12.2. Persistence and degradability

No information available.

# 12.3. Bioaccumulative potential

No information available.

# 12.4. Mobility in soil

No information available.



No. 1907/2006 (REACH)
Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

No information available.

#### 12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

#### 12.6. Other adverse effects

#### **General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**Waste code No.** 07 02 04\*

Name of waste

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

Product rests: send for disposal, e.g. special waste incineration.

### Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

# **SECTION 14: Transport information**

### Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

#### Special precautions for user

No information available.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **VOC** standard

### Remark

Daten separat anfragen / Request data separately.

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

# Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

# **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

### Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 21 Harmful in contact with skin.

R 22 Harmful if swallowed.

R 34 Causes burns.

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



No. 1907/2006 (REACH) Printed 17.05.2013

revision 06.05.2013 (GB) Version 8.0

Plastic-Metal F Hardener (GB)

| H302 | Harmful if swallowed.                              |
|------|----------------------------------------------------|
| H312 | Harmful in contact with skin.                      |
| H314 | Causes severe skin burns and eye damage.           |
| H315 | Causes skin irritation.                            |
| H317 | May cause an allergic skin reaction.               |
| H319 | Causes serious eye irritation.                     |
| H412 | Harmful to aquatic life with long lasting effects. |
|      | 1 0                                                |