

Electro Cleaner

Technical Datasheet

Create Date: 25.06.2013 - Page 1/1

Introduction

Technical sprays are used in nearly all sectors of modern industry. These sprays are used for care and protection of surfaces, for cleaning, degreasing, dissolving and separating and are essential in daily business.



Electro Contact Cleaner is used for fast and efficient cleaning and degreasing of soiled or corroded contacts of all kinds. This special formulation with high-purity solvents removes oxide or sulphide layers, combustion residues as well as resinous or sooty soiling from electro-technical or mechanical parts like measuring instruments, tools, balances, switches, sensors, etc.

Electro Contact Cleaner reduces voltage losses and increases the electric conductivity. Contamination that can cause tracking current is removed.

Applications

Cleaning and degreasing of electro-technical or mechanical parts, like e. g. $\, \bullet \,$ electric machines

- · measuring instruments
- balances
- switches or sensors

Also ideal for all electric connections, contacts, relays and switchboard plants.

Technical data

Colour	colourless
Odour	solvent
Temperature resistance	°C
Shelf life (minimum)	24 months
Special features	high-purity solvents

Processino

Before applying Electro Contact Cleaner, disconnect electric devices from the power line and wait for some minutes until there is no more electric tension inside the machine. Spray a sufficient quantity onto the parts to be cleaned from a distance of 25-30 cm. Electro Contact Cleaner evaporates very quickly and does not leave any residues. Wiping or brushing supports the cleaning effect. Devices should be switched on only when both propellant and active substance have evaporated completely.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation.

We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster P.O. Box 84 60 · DE-48045 Münster Germany

Tel. +49 (0) 251 / 93 22-0 Fax +49 (0) 251 / 93 22-244 Fax +49 (0) 251 / 93 22-233 Export www.weicon.de · info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216 Dubai · U.A.E

Phone +971 4 880 25 05 Fax +971 4 880 25 09 Mobile +971 50 545 99 83 www.weicon.ae · info@weicon.ae

WEICON Inc.

20 Steckle Place · Unit 20 Kitchener · Ontario · N2E 2C3 Canada

Phone +1 519 896 5252 Fax +1 519 896 5254 Cell +1 519 590 5168 www.weicon.ca · info@weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi Arifağa Sokak No: 29 Kat: 3 34530 Yenibosna – Istanbul Turkey www.weicon.biz.tr · info@weicon.biz.tr

WEICON Romania SRL

Str. Depozitelor 22 540240 Targu Mures, jud. Mures Romania www.weicon.com · office@weicon.com