

Anti-Seize -High-Tech- metal-free

Technical Datasheet

Create Date: 25.06.2013 - Page 1/1

Introduction

WEICON Anti-Seize are used as protecting and separating agents, as well as lubricants, for highly stressed parts, especially at high temperatures. Optimally balanced solids contents as well as selected additives permit a wide range of applications, especially in this area.



WEICON Anti-Seize High-Tech is particularly suited if

- metalliferous pastes could cause electrolytic reactions
- nickeliferous products should not or may not be used for health reasons
- dark, metalliferous products should not or may not be used for optical reasons

Technical data

Basic oil	Medicinal oil
Colour	white
OFW device coefficient of friction	0,10 to 0,13
coefficient of friction total	0,13 μ
coefficient of friction thread	0,11 μ
coefficient of friction on upside down	0,14 μ
VKA-Test (DIN 51350) goods load	3600 N
VKA-Test (DIN 51350) welding load	3800 N
VKA-Test (DIN 51350) Spherical cap value (1 Min / 10	0,7 mm
Worked penetration (DIN ISO 2137)	310 to 340 1/10 mm
Sulphur content (DIN 51400)	< 0,1 %
Water resistance (DIN 51807)	1 - 90
Temperature resistance	- 40 to + 1400 °C
Pressure load	230 N/mm ²
Density at +20°C (DIN 51757)	1,42 g/cm ³
Salt spray test (DIN 50017)*	> 170 h
Thermal conductivity	0,7 W/m·K
Dielectric strength	0,40 kV/mm
Specific resistance	1,0 x 10 ¹⁵ Ohm/cm

Pretreatment of the surface

Clean and degrease surfaces. To ensure perfect spraying the product should have room temperature.

Processing

Shake can before use until the mixing ball is heard. Spray on at about 15 cm from surface. ASW 400 is suitable only for assembly paste specific applications, it does not replace pure lubricants and greases.

Storage

Keep in closed original container. Do not store together with oxidizing agents. Keep container tightly closed. Store in a dry place. Recommended storage temperature: room temperature.

Note

Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster
P.O. Box 84 60 · DE-48045 Münster
Germany

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-244
Fax +49 (0) 251 / 93 22-233 Export
www.weicon.de · info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216
Dubai · U.A.E

Phone +971 4 880 25 05
Fax +971 4 880 25 09
Mobile +971 50 545 99 83
www.weicon.ae · info@weicon.ae

WEICON Inc.

20 Steckle Place · Unit 20
Kitchener · Ontario · N2E 2C3
Canada

Phone +1 519 896 5252
Fax +1 519 896 5254
Cell +1 519 590 5168
www.weicon.ca · info@weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi
Arifağa Sokak No: 29 Kat: 3
34530 Yenibosna – İstanbul Turkey
www.weicon.biz.tr · info@weicon.biz.tr

WEICON Romania SRL

Str. Depozitelor 22
540240 Targu Mures, jud. Mures Romania
www.weicon.com · office@weicon.com